

## High performance, intuitive usability, versatile finishing

The imageRUNNER ADVANCE DX 8700 Series delivers high performance and quality black-and-white output for high volume office environments and CRDs. These intelligent systems enhance productivity with versatile finishing options while maintaining an intuitive user experience.



### WORKFLOW EFFICIENCY

- An intuitive user interface with a large, responsive colour touchscreen makes carrying out tasks easy.
- Scalable support for mobile and flexible work styles can increase efficiency by allowing workers to capture or print documents and access certain cloud applications on the go.
- Advanced Personalisation enables a unique, personal experience across a fleet, creating a customized user experience tailored to meet each user's workflow needs.
- Scan and convert documents to Searchable PDF, Microsoft® Word, and Microsoft® PowerPoint files through a single-pass duplexing document feeder that holds up to 200 originals.
- Create professional-looking reports, booklets, newsletters, manuals, proposals, and contracts with flexible finishing options such as professional punching, folding, document insertion, and booklet-making.
- The optional imagePASS print controller, an ideal choice for busy operations, provides robust processing capabilities, variable data printing (VDP), and a print production workflow.

### COST MANAGEMENT

- The ability to apply print policies, monitor output, and restrict usage by user helps reduce unnecessary printing, encourages cost recovery, and can help save money on paper and toner.
- Tight integration with output management solutions, such as uniFLOW, provides the ability to carry out detailed tracking, reporting, and cost analysis.
- Quality and reliability, combined with remote diagnostics and assistance, can help reduce costs by minimizing downtime and time spent by IT resolving issues.
- Consistent user operation combined with remote and centralized fleet management can help simplify IT management of devices and entire fleets.

### SECURITY

- Control who has access to the device with authentication by using the standard Universal Login Manager application.
- Help prevent unauthorized distribution of sensitive information with an array of standard and optional document security features.
- Help ensure information privacy and security across your entire network with IPsec, port filtering capabilities, and SSL technology.

**#WeDeliverReliability**

## DEVICE AND FLEET MANAGEMENT EFFICIENCY

- The ability to pre-configure devices makes installation easy and fleet management is simplified with the capability to synchronize settings across multiple devices.
- Canon's device management tools give you a centralized point of control across your entire fleet, including the ability to check device status and consumables, turn off devices remotely, capture meter readings, as well as manage address books and printer drivers.
- Standard Genuine Adobe PostScript and PCL support integration with enterprise applications and legacy systems to help streamline business processes.

## RELIABILITY

- Canon's signature reliability and engine technologies provide reliable high quality output to meet the needs of busy departments and Central Reprographics Departments (CRDs)/In-plant Printers.

- State-of-the-art imaging technologies and toner allow for consistently striking images in rich black-and-white tones and 1200 dpi print resolution.
- Designed to achieve maximum uptime with status notifications to help keep supplies replenished, intuitive user maintenance videos, the ability to replace toner on the fly, and automatic job re-routing (with optional solutions).

## SUSTAINABILITY

- Fusing technologies, pO toner, and innovative sleep mode features help lower overall energy consumption.
- Help minimize waste with default 2-sided printing, secure printing, and the ability to hold print jobs, preview them and change print settings at the device, helping to achieve the results you want the first time.
- Incorporates sustainable design, with the use of recycled materials and bio-based plastic, and a focus on minimizing environmental impact.
- ENERGY STAR qualified and rated EPEAT Silver.

# MACHINE SPECIFICATION

## MAIN UNIT

### Machine Type

A3 Monochrome Laser Multifunctional

### Core Functions

Print, Copy, Scan, Send, Store and Optional Fax

### Processor

1.75GHz Dual Core Processor

### Control Panel

Standard : 25.6cm(10.1inch) TFT LCD WSVGA Colour Touch panel  
Optional : 26.4cm(10.4inch) TFT LCD SVGA Colour Upright Touch panel

### Memory

Standard: 3.0GB RAM

### Hard Disk Drive

Standard\*: 320GB (Available Disk Space: 250GB)  
Optional : 250GB, 1TB  
\* A different initial HDD may be used.

### Mirroring Hard Disk Drive

Optional

### Interface Connection

#### Network

Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n)

Optional: NFC, Bluetooth Low Energy

#### Others

Standard: USB 2.0 x1 (Host), USB 3.0 x1 (Host), USB 2.0 x1 (Device)

Optional: Serial Interface, Copy Control Interface

### Paper Supply Capacity (A4, 80g/m<sup>2</sup>)

Standard: 4 200 sheets  
100-sheet Multi-purpose tray x1  
1 500-sheet Paper Deck x 2  
550-sheet Paper Cassette x 2  
Maximum: 7 700 sheets (with POD Deck Lite-C1 or POD Deck Unit-E1)

### Paper Output (A4, 80g/m<sup>2</sup>)

250 Sheets (with Copy Tray-R2)  
Maximum: 5 000 sheets (High-Volume Stack mode "ON" with Staple Finisher-W1 PRO or Booklet Finisher-W1 Pro)

### Finishing Capabilities

With options: Collate, Group, Offset, Staple, Saddle Stitch, Hole Punch, Eco Staple, Staple On Demand, Document Insertion, Z-fold, Half-fold, C-fold, Accordion-Z fold, Double Parallel-fold, Trimming

### Supported Media Types

#### Paper Decks (Right/Left):

Thin, Plain, Recycled, Color, Heavy, Bond, Pre-punched, Letterhead

#### Paper Cassettes (Upper/Lower):

Thin, Plain, Recycled, Color, Heavy, Bond, Pre-punched, Letterhead, Tab\*

\*Requires Tab Feeding Attachment-B1.

#### Multi-purpose Tray:

Thin, Plain, Recycled, Color, Heavy, Bond, Transparency, Labels, Pre-punched, Letterhead, Tab

#### Supported Media Sizes

##### Upper Left/Right Cassettes (1/2):

Standard size: A4, B5

##### Lower Cassettes (3/4):

Standard size: SRA3, A3, A4, A4R, A5R, B4, B5, B5R  
Custom size: 139.7 x 182.0mm to 330.2 x 487.7mm

### Multi-purpose Tray:

Standard size: SRA3, A3, A4, A4R, A5\*, A5R, A6R\*, B4, B5, B5R  
Custom Size : 100.0 x 148.0mm to 330.2 x 487.7mm  
Free size: 100.0 x 148.0mm to 330.2 x 487.7mm

\*1 Supported media weights: more than 64g/m<sup>2</sup>  
\*2 Supported media weights: more than 91g/m<sup>2</sup>

### Supported Media Weights

Paper Deck (Right/Left): 52 to 220g/m<sup>2</sup>  
Paper Cassette (Upper/Lower): 52 to 220g/m<sup>2</sup>  
Multi-purpose tray: 52 to 256g/m<sup>2</sup>  
Duplex: 52 to 220g/m<sup>2</sup>

### Warm-up Time

From Power On: 60s or Less\*1  
From Sleep Mode: 60s or Less  
Quick Startup Mode: 4s or Less\*2

\*1\* Time from device power-on, until copy ready (not print reservation)

\*2\* Time from device power on to when the copy icon enabled to operate on the touch panel display

### Dimensions (W x D x H)

Standard: 670mm x 770mm x 1185mm  
(including 1-pass DADF and flat touch panel)  
With optional Upright Control Panel: 1170 x 770 x 1252mm

### Installation Space (W x D)

Basic: 1 535 x 1 353mm (with Multi-purpose tray/upper-right cover open + Front cover open + Copy Tray)  
Fully configured: 5 068 x 1 409mm (with POD Deck Lite-C1 + Document Insertion Unit-N1 + Multifunction Professional Puncher-B1 + Paper Folding Unit-J1 + Booklet Finisher-W1 Pro + Booklet Trimmer-F1 + Main unit Front Cover open)

### Weight

Standard : Approx. 221kg  
With optional Upright Touch Panel: Approx. 225kg

## Printing Specifications

### Print Speed

iR-ADV DX 8705 : Up to 105 pages/min (A4), Up to 54 pages/min (A3), Up to 76 pages/min (A4R), Up to 105 pages/min (A5R)

iR-ADV DX 8795 : Up to 95 pages/min (A4), Up to 50 pages/min (A3), Up to 69 pages/min (A4R), Up to 95 pages/min (A5R)

iR-ADV DX 8786 : Up to 86 pages/min (A4), Up to 44 pages/min (A3), Up to 63 pages/min (A4R), Up to 86 pages/min (A5R)

### Print Resolution (dpi) 1200 x 1200

### Page description languages

Standard : UFR II (standard),  
Optional : PCL 6, Genuine Adobe PostScript Level 3

### Direct Print

Supported file types: PDF, EPS, TIFF/JPEG, and XPS

### Printing from mobile and cloud

AirPrint, Mopria, Google Cloud Print, Canon Print Business, and uniFLOW Online

A range of software and MEAP-based solutions are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information.

### Fonts

PS fonts: 136 Roman  
PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT/J/K/S/T<sup>1</sup> (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts<sup>2</sup>  
\*1 Requires optional PCL INTERNATIONAL FONT SET-A1

\*2 Require optional BARCODE PRINTING KIT-D1

### Printing Features

Secured Print, Secure Watermark, Header/Footer, Page Layout, Two-sided Printing, Mixed Paper Sizes/Orientations, Front/Back Covers, Toner Reduction, Poster Printing, Forced Hold printing, Print Date, Scheduled Printing, Printing Using a Virtual Printer.

### Operating System

UFR II : Windows®7/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016/Server 2019, MAC OS X (10.10 or later)

PCL : Windows®7/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016/Server 2019

PS : Windows®7/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016/Server 2019, MAC OS X (10.10 or later)

PPD : Windows®7/8.1/10, MAC OS X (10.9 or later)

## Copy Specifications

### Copy Speed

iR-ADV DX 8705 : Up to 105 pages/min (A4), Up to 54 pages/min (A3), Up to 76 pages/min (A4R), Up to 105 pages/min (A5R)

iR-ADV DX 8795 : Up to 95 pages/min (A4), Up to 50 pages/min (A3), Up to 69 pages/min (A4R), Up to 95 pages/min (A5R)

iR-ADV DX 8786 : Up to 86 pages/min (A4), Up to 44 pages/min (A3), Up to 63 pages/min (A4R), Up to 86 pages/min (A5R)

### First-Copy-Out Time (A4) Approx. 2.7s or less

### Copy Resolution (dpi) 600 x 600

Multiple Copies Up to 9 999 copies

### Copy Density

Automatic or Manual (9 Levels)

### Magnification

Variable zoom: 25% - 400% (1% Increments)  
Preset reduction/enlargement: 25%, 50%, 61%, 70%, 81%, 86%, 100% (1:1), 115%, 122%, 141%, 200%, 400%

## Scan Specifications

### Type

Single-pass Duplexing Automatic Document Feeder \* [2-sided to 2-sided (Automatic)]

\* Detect Feeder Multi Sheet Feed is supported.

### Document Feeder Paper Capacity (80g/m<sup>2</sup>)

up to 200 sheets

### Acceptable Originals and Weights

Platen: Sheet, Book, and 3-Dimensional objects

Document Feeder media weight:

1-sided scanning\*: 38 to 220g/m<sup>2</sup>

2-sided scanning\*: 38 to 220g/m<sup>2</sup>

\*An acceptable weights of A6R or smaller is 50 to 220g/m<sup>2</sup>.

### Supported Media Sizes

Platen: max. scanning size: up to 297.0 x 431.8mm

Document Feeder media size:

A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, B6R,  
Custom size: 70.0 x 139.7mm to 304.8 x 431.8mm

### Scan Speed (ipm: BW/CL; A4)

Single Pass DADF-C1:

1-sided Scanning : 135/135 (300 x 300dpi, send),

135/80 (600 x 600dpi, copy)

2-sided Scanning : 270/270 (300 x 300dpi, send),

165/90 (600 x 600dpi, copy)

### Scan Resolution (dpi)

Scan for Copy : 600 x 600

Scan for Send : (Push) 600 x 600 (SMB/FTP/WebDAV/  
iFAX), (Pull) 600 x 600

Scan for Fax : 600 x 600

**Pull Scan Spec**  
 Colour Network ScanGear2. For both TWAIN and WIA  
 Supported OS: Windows® 7/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016

## Send Specifications

**Destination**  
 E-mail/Internet FAX (SMTP), SMB3.0, FTP, WebDAV, Mail Box, Super G3 FAX (Optional), IP Fax (Optional)

**Address Book**  
 LDAP (2 000)/Local (1 600)/Speed dial (200)

**Send Resolution (dpi)**  
 Push : up to 600 x 600  
 Pull : up to 600 x 600

**Communication Protocol**  
 File : FTP (TCP/IP), SMB3.0 (TCP/IP), WebDAV  
 E-mail/fax : SMTP, POP3

**File Format**  
 Standard : TIFF, JPEG, PDF (Limited Color, Compact, Searchable, Apply policy, Optimize for Web, PDF/A-1b, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS (Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word)

## Fax Specifications

**Maximum Number of Connection Lines** 4  
**Modem Speed** Super G3 : 33.6kbps  
 G3 : 14.4kbps  
**Compression Method** MH, MR, MMR, JBIG  
**Resolution (dpi):** 400x400 (Ultra Fine),  
 200x400 (Super Fine),  
 200x200 (Fine),  
 200x100 (Normal)  
**Sending/Receiving Size**  
 Sending : A3, A4, A4R, A5\*1, A5R\*1, B4, B5\*2, B5R\*1  
 Receiving : A3, A4, A4R, A5R, B4, B5, B5R  
 \*1 Sent as A4 \*2 Sent as B4 short  
**FAX Memory** Up to 30 000 pages (2 000 jobs)  
**Speed Dials** Max. 200  
**Group Dials/Destinations** Max. 199 dials  
**Sequential Broadcast** Max. 256 addresses  
**Memory Backup** Yes

## Store Specifications

**Mail Box Simple (Number supported)**  
 100 User Inboxes, 1 Memory RX Inbox,  
 50 Confidential Fax Inboxes  
 30 000 Maximum Pages (2 000 jobs) Stored

**Advanced Box**  
 Communication Protocol: SMB or WebDAV  
 Supported Client PC: Windows (Windows® 8.1/10)  
 Concurrent Connections (Max.): SMB: 64, WebDAV: 3

**Advanced Box Available Disc Space**  
 Approx. 16GB (Standard HDD)  
 Approx. 480GB (with option 1TB HDD)

## Security Specifications

**Authentication**  
 Standard : User Authentication (Picture Login, Picture and PIN Login, Card Login, Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online Express (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Access Management System (Access Control)

**Document Security**  
**Print Security** (Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print™)  
**Receive Data Security** (Confidential Fax Inbox Forwarding Received Documents Automatically)  
**Scan Security** (Encrypted PDF, Device Signature PDF/XPS,

User Signature PDF/XPS, Adobe LiveCycle® Rights Management ES2.5 Integration), BOX Security (Mail Box Password Protected, Advanced Box Access Control)  
**Send Data Security** (Setting for requesting password input per transmission, Restricted E-mail/File send functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support), Scan Lock (QR code), Document Tracking (Secure Watermark)  
 \*1 Requires uniFLOW Online/uniFLOW

**Network Security**  
 TLS 1.3, IPsec, IEEE802.1X authentication, SNMP V3.0, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), Disabling Unused Functions (Enabling/Disabling Protocols/Applications, Enabling/Disabling Remote UI, Enabling/Disabling USB Interface)

**Device Security**  
 Protecting HDD Data (HDD Data Encryption (FIPS140-2 Validated), HDD Data Overwrite Erase, HDD Lock), Standard HDD Initialize, Trusted Platform Module (TPM), Job Log Conceal Function, Protecting MFD Software Integrity, Checking MFD Software Integrity (Verify System at Startup, Runtime Intrusion Detection), Optional: IEEE2600.2 (Common Criteria Certification) (available at a later schedule)

**Device Management and Auditing**  
 Administrator Password, Digital Certificate And Key Management, Audit Log, Cooperating with External Security Audit System (Security Information and Event Management), Image Data Logging, Security Policy Setting

## Environment Specifications

**Operating Environment**  
 Temperature: 10 to 30°C  
 Humidity: 20 to 80%RH (Relative Humidity)

**Power Source** 220-240V, 50-60Hz, 10A

**Power Consumption**  
 Maximum: 2 400W  
 Standby: Approx. 217W\*1  
 Sleep mode: Approx. 0.9W\*2  
 \*1 Reference Value  
 \*2 0.9W sleep mode is not available in all circumstances due to certain settings.

## Software and Printer Management

**Tracking and reporting**  
 Universal Login Manager (ULM)  
 uniFLOW Online Express

**Remote Management Tools**  
 iW Management Console  
 eMaintenance  
 Content Delivery System

**Scanning Software**  
 Network ScanGear

**Optimisation Tools**  
 Canon Driver Configuration Tool  
 NetSpot Device Installer

**Platform**  
 MEAP (Multifunctional Embedded Application Platform)

**Document Publishing**  
 IW DESKTOP

## Paper Supply Options

**PAPER DECK UNIT-E1**  
 Paper Capacity : 3 500 Sheets (80g/m<sup>2</sup>)  
 Paper Type : Thin, Plain, Recycled, Color, Heavy, Bond, Pre-punched, Letterhead  
 Paper Size : A4, B5  
 Paper Weight : 52 to 256 g/m<sup>2</sup>  
 Power Source : From the Main Unit  
 Dimensions (WxDxH) : 340 x 630 x 572mm (attached to the main unit)  
 Weight : Approx. 34kg

**POD DECK LITE-C1**  
 Paper Capacity : 3 500 sheets (80 g/m<sup>2</sup>)  
 Paper Type : Thin, Plain, Recycled, Color, Heavy, Tracing, Bond, Transparency, Label, Pre-punched, Letterhead, Tab  
 Paper Size : A3, A4, A4R, A5R, B4, B5, B5R  
 Custom size : 139.7 x 182.0mm to 330.2 to 487.7mm  
 Paper Weight : 52 to 256 g/m<sup>2</sup>  
 Power Source : 220-240V, 50/60Hz, 1.2A  
 Dimensions (WxDxH) : 633 x 686 x 574mm (attached to the main unit)  
 Weight : Approx. 68kg

## Hardware Accessories

**Card Readers**  
 COPY CARD READER-F1  
 COPY CARD READER ATTACHMENT-A4

**Others**  
 UPRIGHT CONTROL PANEL-J1  
 UTILITY TRAY-B1  
 TAB FEEDING ATTACHMENT KIT-B1  
 SHIFT TRAY-F1  
 NUMERIC KEYPAD-A1  
 FINISHER JOGGER KIT-A1

## Security Options

**Device Security**  
 iR-ADV SECURITY KIT-AJ1 FOR IEEE 2600 COMMON CRITERIA CERTIFICATION (available at a later schedule)

**Data Security**  
 2.5INCH/250GB HDD-N1  
 2.5INCH/1TB HDD-P1  
 HDD MIRRORING KIT-J1

## System and Controller Options

**Print Accessories**  
 PCL INTERNATIONAL FONT SET-A1  
 PCL ASIAN FONT SET-A1  
 PCL PRINTER KIT-BD1  
 PS PRINTER KIT-BD1

**Barcode Printing**  
 BARCODE PRINTING KIT-D1

**Efi-Fiery Based Controller**  
 imagePASS-Y3 V1.1  
 FIERY IMPOSE  
 FIERY COMPOSE  
 FIERY IMPOSE AND COMPOSE  
 FIERY IMAGEVIEWER  
 REMOVABLE HDD KIT-B6

**System Accessories**  
 SERIAL INTERFACE KIT-K3  
 NFC KIT-E1  
 COPY CONTROL INTERFACE KIT-A1  
 CONNECTION KIT-A2 FOR BLUETOOTH LE

**Fax Accessories**  
 SUPER G3 FAX BOARD-AS1  
 SUPER G3 2ND LINE FAX BOARD-AS1  
 SUPER G3 3RD/4TH LINE FAX BOARD-AS1  
 REMOTE FAX KIT-A1  
 IP FAX EXPANSION KIT-B1

## Other Options

**Accessibility Accessories**  
 ADF ACCESS HANDLE-A1  
 VOICE GUIDANCE KIT-G1  
 VOICE OPERATION KIT-D1

**Consumables**  
 STAPLE-N1  
 STAPLE P1  
 STAPLE-CARTRIDGE-X1  
 STAPLE CARTRIDGE-Y1

For full specifications, please refer to the specification table on your local Canon web site.

## CONTROLLER SPECIFICATION - imagePASS Y3 v1.1 (External)



**Optional/Standard**  
 On All Models  
**Print Resolution (dpi)**  
 1200 x 1200,  
 600 x 600  
**Page Description Language(s)**  
 PCL6, Adobe PostScript 3  
**Memory**  
 8GB (2 x 4GB)  
**Hard Disk Drive**  
 500 GB SATA  
**Processor**  
 Intel Pentium G4400 (3.3 GHz)

**System**  
 Fiery FS350 Pro

**Fonts**  
 PS : 138 Fonts  
 PCL : 113 Fonts

**Supported Operating Systems**  
 Windows 7 64 bit/Windows 8.1 64 bit/Windows 10 64 bit/Windows Server 2008 R2 64 bit only/Windows Server 2012 64 bit only (Only Printer driver support)/Windows Server 2012 R2 64 bit only/Windows Server 2016 R2 64 bit only, MAC OS (10.11, 10.12, 10.13, 10.4)

**Interface**  
 2 x Ethernet (1000Base-T/100Base-TX/10Base-T), USB 3.0 x 2 (rear), x 3 (front on Fiery Quick Touch TM), USB 2.0 x4 (rear)

**Network protocols**  
 TCP/IP (FTP, SMTP, POP, HTTP, SNMP, LDAP, SLP, SMB, LPD, IPP, WS-Discovery, Bonjour, Direct Mobile Printing, Port9100, SNT, 802.1X, DHCP, DNS, NTP)

**Direct Print**  
 PDF1.7, EPS, TIFF6, JDF1.4/JMF (Optional)

**VDP**  
 FreeForm v1, v2.1, PPML, PDF/VT-1, PDF/VT-2, Creo VPS

**Fiery Print Controller Standard Features**  
 Fiery Command WorkStation6 /Paper Catalog, Fiery Remote Scan/Fiery Hot Folders & Virtual Printers/Fiery JDF

**Fiery Print Controller Options**  
 Fiery Impose/Fiery Compose /Fiery Impose and Compose/Removable HDD kit/Fiery Image Viewer

**HW Platform**  
 NX One

**Base OS**  
 Windows 10 IoT Enterprise 2019 LTSC

**Power Source**  
 AC100-240V, 50Hz/60Hz, 3.0A (100V) - 1.5A (240V)

**Maximum Power Consumption**  
 53 W

**Dimensions (W x D x H)**  
 203 x 248 x 384 mm



**Weight** Approx. 5.9 kg

# MAIN CONFIGURATION OPTIONS

## MFP MODEL




**UPRIGHT CONTROL PANEL**  
Optional

**PAPER DECK UNIT-E1**  
· 3 500-sheet capacity  
· Supports A4/B5

**POD DECK LITE-C1**  
· 3 500-sheet capacity  
· 52 to 256g/m<sup>2</sup>  
· Supports up to SRA3  
· User adjustable



**BASIC OUTPUT OPTION**

**COPY TRAY-R2**  
1-sided-250 Sheets (80g/m<sup>2</sup>)  
2-sided-100 Sheets (80g/m<sup>2</sup>)

## FINISHER SPECIFICATION



**BOOKLET FINISHER-AC 1 (External) (iR-ADV 8786 only)**

- 3-trays, 3 500 -sheet capacity
- Paper Weight: 52 - 256g/m<sup>2</sup>
- Corner and double stapling up to 65 sheets (90g/m<sup>2</sup>) 20 x 10 sets (52-105g/m<sup>2</sup>)
- Booklet-making up to 20 sheets
- Dimensions (W x D x H): 656mm x 623mm x 1 195mm
- Weight: Approx. 60kg
- Supports Eco Stapling and Staple On Demand
- Supports optional 2/4 and 2/3 Hole inner Puncher - 2/4 Hole Puncher Unit-A1 and 2/3 Hole Puncher Unit-A1



**STAPLE FINISHER - AC 1 (External) (iR-ADV 8786 only)**

- 3-tray, 3 500 -sheet capacity
- Paper Weight: 52 - 256g/m<sup>2</sup>
- Corner and double stapling up to 65 sheets (90g/m<sup>2</sup>)
- Dimensions (W x D x H): 656mm x 623 mm x 1 195mm
- Weight: Approx. 36kg
- Supports Eco Stapling and Staple On Demand
- Supports optional 2/4 and 2/3 hole inner Puncher - 2/4 Hole Puncher Unit-A1 and 2/3 Hole Puncher-A1



**BOOKLET FINISHER-X1 (External)**

- 3-tray, 4 250-sheet capacity
- Paper Weight: 52 - 256g/m<sup>2</sup>
- Corner and double stapling up to 100 sheets (80g/m<sup>2</sup>) 20 sheets x 5 sets (60-80g/m<sup>2</sup>)
- Booklet-making up to 20 sheets and saddle-folding up to 5 sheets
- Power Source: 100-240V AC, 50-60 Hz, 2.8A
- Dimensions (W x D x H): 896mm x 765mm x 1 040mm
- Weight: Approx. 110kg
- Supports optional internal 2/4, S4 and 2/3 Holes 4-hole puncher (Puncher Unit-BF1 & BG1) and booklet trimming (Inner Booklet Trimmer-A1)



**STAPLE FINISHER-X1 (External)**

- 3-tray, 4 250-sheet capacity
- Paper Weight: 52 - 256g/m<sup>2</sup>
- Corner and double stapling up to 100 sheets (80g/m<sup>2</sup>)
- Power Source: 100-240V AC, 50-60 Hz, 2.8A
- Dimensions (W x D x H): 782mm x 765mm x 1 040mm
- Weight: Approx. 64kg
- Supports optional internal 2/3 and 2/F4-hole puncher (Puncher Unit-BF1 and BG1)



**MULTI FUNCTION PROFESSIONAL PUNCHER-B1**

- Supports various die sets
- Up to 300g/m<sup>2</sup>
- Supports SRA3, A3, A4, A4R
- Dimensions (W x D x H): 445mm x 795mm x 1 040mm



**DOCUMENT INSERTION UNIT-N1**

- Insert preprinted sheets
- Up to SRA3, A3, A4, A4R, B4, B5, B5R
- Custom size 182 x 182mm to 330.2 x 487.7mm
- 2 trays
- 400-sheet total capacity
- Dimension (W x D x H): 336 x 793 x 1 407mm



**PAPER FOLDING UNIT-J1**

- Z-fold, C-fold, Half-fold, Accordion Z-fold (52-105g/m<sup>2</sup>)
- Double-parallel fold (52-105g/m<sup>2</sup>)



**BOOKLET TRIMMER-F1**  
\*Require Booklet Finisher-W1 PRO



**BOOKLET FINISHER-W1 PRO (External)**

- 2-tray, 5 000-sheet capacity
- Paper Weight: 52 - 256g/m<sup>2</sup>
- Corner and double stapling up to 100 sheets (80g/m<sup>2</sup>)
- Booklet-making up to 25 sheets X 10 sets (52-80g/m<sup>2</sup>) and saddle-folding up to 5 sheets
- Power Source 220-240V, 50-60 Hz, 8A
- Dimensions (W x D x H): 1 060mm x 792mm x 1 239mm
- Weight: Approx. 182kg
- Supports optional internal 2/4 and 2/3-hole puncher (Puncher Unit-BT1, BU1 and BS1) and optional booklet trimming (Booklet Trimmer-D1)
- Precise output stacking alignment
- Enhanced durability for high volumes



**STAPLE FINISHER-W1 PRO (External)**

- 2-tray, 5 000-sheet capacity
- Paper Weight: 52 - 256g/m<sup>2</sup>
- Corner and double stapling up to 100 sheets
- Power Source: 220-240V, 50-60 Hz, 8A
- Dimensions (W x D x H): 890 mm x 792 mm x 1 239mm
- Weight: Approx. 130kg
- Supports optional internal 2/F4 and S4 Holes and 2/3 hole puncher (Puncher Unit-BU1 and BS1)
- Precise output stacking alignment
- Enhanced durability for high volumes



### Head Office:

Canon India Private Limited, 7th Floor, Tower-B, Building No. 5, DLF Phase III, Gurgaon - 122002  
☎ 0124-486 1265 | 1860 180 3366 | 1800 208 3366 🌐 <https://in.canon/ppp> ✉ [cipl.ppp@canon.co.in](mailto:cipl.ppp@canon.co.in)

### Region/Branch Office:

Delhi/NCR, Hyderabad, Mumbai, Chennai, Bangalore, Kolkata, Pune

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weights and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.

All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. Canon, imageRUNNER, imageRUNNER ADVANCE, imageCHIP, RAPID Fusing System, MEAP, eMaintenance, iW, Business function can be simple and get Smart get genuine are trademarks of Canon Inc. and/or its affiliates. "MEAP" is a trademark of CANON Inc., referring to an "application platform" for Canon multifunction and single function printers. Other names may be the trademarks of their respective owners.

 Canon India Complies with E-Waste (Management) Rules, 2016  
Please return end-of-life product for environmentally safe disposal. For details visit [in.canon](http://in.canon)

This document is for information purpose only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and products names are trademarks and/or registered trademarks of their respective owners.  
Warnings: Unauthorized recording of copyrighted materials may infringe on the rights of copyright owners and be contrary to copyright laws.